


## CHT-2051

## FLUSH STUCCO ALUMINUM INSULATED DOOR

### SERIES FEATURES


- 2"(50.8mm) - Thick CFC-Free Polyurethane
- 17.66 Calculated R-Value
- .057 Calculated U-Value
- 24-Gauge Stucco Aluminum
- Air Infiltration Seal
- Full Thermal Break
- Available with Wind Load
- 2 Color Options
- Industry Leading Warranty
- 10-Year Corrosion & Delamination
- 6-Year Hardware
- 3-Year Spring

### Cross Section



**2" (50.8mm)  
Thick Sections**

### AVAILABLE COLORS



Colors are not exact due to the differences in monitor and printer calibrations. For accurate color samples, contact Haas Door for a metal color selector. Trinar® colors carry a 35 year paint warranty.

### MODEL FEATURES

- 16ga. Galvanized Steel End Stiles
- Flush stucco embossment outside, V-groove stucco embossement inside
- Tongue and groove section joint

### Exterior View



### Interior View



### 2000 SERIES LINKS

*Click links for info.*

[HOMEPAGE](#)

[BIM](#)

[BROCHURE](#)

[SPECS](#)

[GALLERY](#)

[SPECWIZARD](#)

[CAD](#)

[CATALOG](#)

Rev. 2.1 – October 2017