


**CHT-2082**

**RIBBED SHORT WOOD GRAIN PANEL STEEL INSULATED DOOR**

**SERIES FEATURES**

- 2"(50.8mm) - Thick CFC-Free Polyurethane
- 17.66 Calculated R-Value
- .057 Calculated U-Value
- 26-Gauge Galvanized Steel
- Air Infiltration Seal
- Meets ASHRAE 90.1 Air Infiltration Requirements
- Full Thermal Break
- Available with Wind Load
- 21 Color Options
- 10-Year Rust & Delamination Warranty
- 1-Year Hardware
- 1-Year Spring

**Cross Section**



**2" (50.8mm)  
Thick Sections**

**AVAILABLE COLORS**



Colors are not exact due to the differences in monitor and printer calibrations. For accurate color samples, contact Haas Door for a metal color selector. Trinar® colors carry a 35 year paint warranty.

**MODEL FEATURES**

- Extruded End Cap
- Ribbed Short Panel wood grain embossment on outside, V-Groove pattern wood grain embossment on inside
- Tongue and groove section joint

**Exterior View**



**Interior View**



**2000 SERIES LINKS**

*Click links for info.*

**HOMEPAGE**

**BIM**

**BROCHURE**

**SPECS**

**GALLERY**

**SPECWIZARD**

**CAD**

**CATALOG**

Rev. 2.1 – October 2017