

Specification Sheet: Model 5950 Steel Long Panel Carriage House Residential Door

Door Sections:

Panels: 18" or 21" high by width of door.
Panel Material: 25 gauge deep-draw quality steel. Hot dipped galvanized G40 coating. Exterior: polyester primer and topcoat available in white, almond, sandstone, brown or desert tan. Painted Woodtones available in classic woodgrain and modern woodgrain. Interior: white polyester primer and topcoat.
Section Thickness: 2"
Panel Profile: Woodgrain textured, long panel carriage house embossed.
Joint Design: Tongue and groove rails.
End Stiles: Wrap-around style, 20 gauge galvanized steel, full height of section. Secured to inside rails using Tab-Lock system and interlocked to face of section.
Center Stiles: 20 gauge galvanized steel full height of section. Secured to inside rails using Tab-Lock system and secured to face of section with industrial adhesive.
Insulation: Not available.

Tracks: **Vertical Tracks:** Roll-formed 17 gauge galvanized steel for doors through 7'-0" in height. Doors over 7'-0" through 10'-0" will be 16 gauge. Doors over 10'-0" will be 14 gauge. Tracks to be mounted with track brackets (bolted or riveted to track) and lag-bolted to jamb. Tracks are adjustable (if bolted) to ensure weather-tight fit.
Horizontal Tracks: Roll-formed 16 gauge galvanized steel for doors through 10'-0" in height. Doors over 10'-0" will be 14 gauge. Tracks are reinforced with angle (min 14 gauge) according to door size and weight.

Hardware: Graduated heavy duty hinges (min 14 gauge), top fixtures (min 14 gauge) and bottom fixtures (min 13 gauge) are made of galvanized steel. Rollers have 10 ball bearings with casehardened steel tire on a solid steel shaft. Optional Black Spade decorative hardware w/rivets.

Spring Counterbalance: Oil tempered torsion springs are mounted on a cross-header shaft supported by galvanized steel ball bearing end plates and center bracket(s). Springs are custom designed for exact door weight, size and trajectory in accordance with current ANSI 102 standards for a minimum of 10,000 cycles. Counterbalance is transferred through galvanized aircraft quality cables secured to bottom of door.

Trussing: Galvanized trussing provided according to door size and design.

Weather-seal: Double contact vinyl floor seal full width of door. Optional header and jamb seals.

Locking: Optional inside side lock or outside center lock with automatic latch.

Window Lites: Optional 1/8" single pane DSB, glue chip or tinted glass. Lites can be provided with decorative inserts.

Installation / Framing: Torsion spring mounting pads, jamb plates, header plates and associated track system hangers shall be furnished by other than C.H.I. All installation quality and workmanship is responsibility of Contractor and is to be executed in accordance with C.H.I. installation instructions, local and state building codes and work site safety regulations.