

CHT-814 FLUSH WOOD GRAIN STEEL INSULATED DOOR

SERIES FEATURES

- 3"(76.2mm) - Thick CFC-Free Polyurethane
- 25.8 Calculated R-Value
- .039 Calculated U-Value
- 26-Gauge Galvanized Steel
- Air Infiltration Seal
- Full Thermal Break
- Available with Wind Load
- 16 Color Options
- Industry Leading Warranty
- 10-Year Rust & Delamination
- 6-Year Hardware
- 3-Year Spring

Cross Section



**3" (76.2mm)
Thick Sections**

AVAILABLE COLORS



Colors are not exact due to the differences in monitor and printer calibrations. For accurate color samples, contact Haas Door for a metal color selector. Trinar® colors carry a 35 year paint warranty.

MODEL FEATURES

- 16ga. Galvanized Steel End Stiles
- Flush wood grain embossment outside, V-groove pattern wood grain embossment inside
- Tongue and groove section joint

Exterior View



Interior View



800 SERIES LINKS

Click links for info.

[HOMEPAGE](#)

[BIM](#)

[BROCHURE](#)

[SPECS](#)

[GALLERY](#)

[SPECWIZARD](#)

[CAD](#)

[CATALOG](#)

Rev. 2.1 – October 2017